(CEMENTING COMPANY AND OPERATOR MUST COMPLY WITH THE INSTRUCTIONS ON REVERSE SIDE HEREOF)

(or bottom of coller) outside casing? Yes or No

26 Remarks	~27 Kemarks
	*
•	
,	0
•	00053
CEMENTING COMPANY	* <u>OPERATOR</u>
I declare under applicable Corporation Commission rule, that I am authorized to make this certification, that the cementing of casing in this well as shown in the report was performed by me or under my supervision, and that the cementing data and facts presented on both sides of this form are true, correct and complete to the less of m knowledge. This certification covers cementing data only.	I declare under applicable Corporation Commission rule, that I am authorized to make this certification, that I have knowledge of the well data and information presented in this report, and that data and facts presented on both sides of this form are true, correct and complete to the best of my knowledge. This certification covers all yell days and information presented herein.
Jerrel SHirley, Cementer	*Signature of Operator or Authorized Repres. R. M. Helton, a general partner of HELTON OIL CO.
Name of person and Title (Type or Print)	*Name of Person and Title (Type or Print)
Minderman Frac & Cement	ditto, the above.
Cementing Company	*Operator
P. O. BOX 626	713 Lamar St.,
Street Address or P. O Box : r., cc	*Street Address or P. O Box
Electra, Texas 76360	Wichita Falls, TX 76301
City State Zip	*City State Zip
Telephone 817 495'- 3322'	Telephone 817-723-0729 Office. 817-766-2828 Residence. Area Code
	11-2-92.

INSTRUCTIONS

Date

- 1. a) This form shall be filed by the operator, at the O.C.C. office in Oklahoma City, as an attachment to the Completion Report for a producing well or a dry hole.
 - b) An original and one copy of this form shall be filed as an attachment to the Completion Report. (form 1002-A) for each cementing company used on a well.
 - c) The cementing of different casing strings on a well by one cementing company may be consolidated on one form (to be filed in duplicate).
- 2 Cementing Company and Operator shall comply with the applicable portions of O.C.C Rule 3-206

Date

- 3 Set surface casing 50 feet below depth of treatable water to be protected and cement from casing shoe to ground surface or as allowed by Rule 3-206
- 4 IF SETTING ANYTHING OTHER THAN THE FULL AMOUNT OF SURFACE CASING, BE SURE TO FOLLOW THE CORPORATION COMMISSION REGULATIONS