API NUMBER: 007 25618 A

OKLAHOMA CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION P.O. BOX 52000 OKLAHOMA CITY, OK 73152-2000 (Rule 165:10-3-1)

Approval Date: 06/18/2013
Expiration Date: 12/18/2013

Horizontal Hole Oil & Gas

Amend reason: SURFACE LOCATION IS SHIFTING 70' TO THE

AMEND PERMIT TO DRILL

FROM

WEST

01.										
WELL LOCATION:	Sec:	08	Twp:	3N	Rge:	23E	СМ	County:	BEAV	/ER
SPOT LOCATION:	SE	SE	S	W	SW		FEET FROM QUA	ARTER:	FROM	SOUTH

SECTION LINES: 250 1120

Lease Name: CALDWELL TRUSTS Well No: 1-17XLH Well will be 250 feet from nearest unit or lease boundary.

Operator CABOT OIL & GAS CORPORATION Telephone: 2818482620 OTC/OCC Number: 18246 0

CABOT OIL & GAS CORPORATION 840 GESSNER RD STE 1200

HOUSTON, TX 77024-4142

LEON FLOYD SPANGLER

ROUTE BOX

BEAVER OK 73932

Formation(s) (Permit Valid for Listed Formations Only):

	Name	Depth	Name	Depth
1	MARMATON	6015 6	3	
2		7	•	
3		8	3	
4		9)	
5		1	0	
Spacing Orders:	601146	Location Exception Orders:		Increased Density Orders:

Pending CD Numbers: 201303066 Special Orders:

Total Depth: 16700 Ground Elevation: 2635 Surface Casing: 1700 Depth to base of Treatable Water-Bearing FM: 310

Under Federal Jurisdiction: No Fresh Water Supply Well Drilled: Yes Surface Water used to Drill: No

PIT 1 INFORMATION Approved Method for disposal of Drilling Fluids:

Type of Pit System: CLOSED Closed System Means Steel Pits
Type of Mud System: WATER BASED

Chlorides Max: 60000 Average: 5000

Is depth to top of ground water greater than 10ft below base of pit? Y

3 depth to top of ground water greater than 101 below base of pit:

Within 1 mile of municipal water well? N
Wellhead Protection Area? N

Pit is located in a Hydrologically Sensitive Area.

Category of Pit: C

Liner not required for Category: C

Pit Location is BED AQUIFER

Pit Location Formation: OGALLALA

D. One time land application -- (REQUIRES PERMIT)
H. CLOSED SYSTEM=STEEL PITS PER OPERATOR OPTION

PERMIT NO: 13-23107

HORIZONTAL HOLE 1

Sec 20 Twp 3N Rge 23E County BEAVER

Spot Location of End Point: W2 SE SW SW
Feet From: SOUTH 1/4 Section Line: 330
Feet From: WEST 1/4 Section Line: 750

Depth of Deviation: 5001 Radius of Turn: 1178

Direction: 180
Total Length: 9569

Measured Total Depth: 16700

True Vertical Depth: 6178

End Point Location from Lease,
Unit, or Property Line: 330

Notes:

Category Description

DEEP SURFACE CASING 6/17/2013 - G71 - APPROVED CONTINGENT ON NOTIFYING OCC FIELD STAFF IMMEDIATELY

OF ANY LOSS OF CIRCULATION OR FAILURE TO CIRCULATE CEMENT TO SURFACE ON ANY

CONDUCTOR OR SURFACE CASING

PENDING CD - 201303066 6/17/2013 - G30 - W2 17 & W2 20-3N-23ECM

X601146 MRMN

COMP. INT. NCT 330 FNL, NCT 660 FSL, NCT 330 FSL OF W2 17 & W2 20

NO OP. NAMED REC 6/6/13 (M.PORTER)

SPACING - 601146 6/17/2013 - G30 - (640 HOR) W2 17 & W2 20-3N-23ECM

EXT 586461/597829 MRMN POE TO BHL: NCT 660' FB

(SUPERSEDE NON-DEVELOPED NON-HORIZONTAL SPACING UNITS)