API NUMBER: 125 01220 A

OKLAHOMA CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION P.O. BOX 52000 OKLAHOMA CITY, OK 73152-2000 (Rule 165:10-3-1)

Approval Date:	09/09/2013
Expiration Date:	03/09/2014

Straight Hole Oil & Gas

PERMIT TO RE-ENTER

ELL LOCATION: Sec: 16	Twp: 8N Rge: 5E		TAWATOMIE		
OT LOCATION: C SE	E NW SE	FEET FROM QUARTER: FROM	SOUTH FROM WEST		
		SECTION LINES:	1650 990		
Lease Name: SCHOOL LAN	ND	Well No:	1	Well will be	330 feet from nearest unit or lease boundary
Operator WIECK OIL Name:	L COMPANY LLC		Telephone: 40530831	58	OTC/OCC Number: 22741 0
WIECK OIL COMPAI P.O. BOX 165 CROMWELL,	NY LLC OK	74837-0165		OMMISSIONERS O 20 N ROBINSON, S	F THE LAND OFFICE UITE 1000W
Ortomiveze,			C	KC	OK 73102
Name HUNTON HUNTON Hunton Figure 1 Hunton Hunton Hunton		Depth 4070	6 7 8 9 10	Name	Depth
			Ordoro	t.	creased Density Orders:
acing Orders: No Spacing		Location Exception	Orders.	ır	icreased Density Orders.
No Spacing		Location Exception	Orders.		pecial Orders:
nding CD Numbers:	Ground Elevation: 92		Casing: 0	s	·
no spacing nding CD Numbers: Total Depth: 4200 Cement will be circul	lated by use of a tv	Surface wo-stage cementing t	Casing: 0	s	pecial Orders: to base of Treatable Water-Bearing FM: 990
no spacing Iding CD Numbers: Fotal Depth: 4200 Cement will be circul	lated by use of a tv	Surface wo-stage cementing t	Casing: 0 tool from 1090 to Supply Well Drilled: No	Depth	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No
no spacing Inding CD Numbers: Total Depth: 4200 Cement will be circul Under Federal Jurisdiction: T 1 INFORMATION	lated by use of a to	Surface (wo-stage cementing to	Casing: 0 tool from 1090 to Supply Well Drilled: No	S Depth	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No
not spacing Inding CD Numbers: Total Depth: 4200 Cement will be circul Under Federal Jurisdiction: IT 1 INFORMATION IT of Pit System: CLOSED	lated by use of a to	Surface (wo-stage cementing to	Casing: 0 tool from 1090 to Supply Well Drilled: No	Depth	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No
no spacing Inding CD Numbers: Total Depth: 4200 Cement will be circul Under Federal Jurisdiction: T 1 INFORMATION Type of Pit System: CLOSED Type of Mud System: WATER	lated by use of a to No Closed System Means S	Surface (wo-stage cementing to	Casing: 0 tool from 1090 to Supply Well Drilled: No Approved	Depth O 0 . Method for disposal of Drillin	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No
Cement will be circul Under Federal Jurisdiction: T 1 INFORMATION pe of Pit System: CLOSED pe of Mud System: WATER slorides Max: 8000 Average:	No Closed System Means S R BASED 5000 greater than 10ft below ba	Surface (wo-stage cementing to Fresh Water Steel Pits	Casing: 0 tool from 1090 to r Supply Well Drilled: No Approved	Depth O 0 . Method for disposal of Drillin Commercial pit facility: Sec	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No
Cement will be circul Under Federal Jurisdiction: T 1 INFORMATION pe of Pit System: CLOSED pe of Mud System: WATER shorides Max: 8000 Average: depth to top of ground water of thin 1 mile of municipal water	lated by use of a to No Closed System Means S R BASED 5000 greater than 10ft below bar well? N	Surface (wo-stage cementing to Fresh Water Steel Pits	Casing: 0 tool from 1090 to r Supply Well Drilled: No Approved	Depth O 0 . Method for disposal of Drillin Commercial pit facility: Sec	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No ng Fluids:
Cement will be circul Under Federal Jurisdiction: IT 1 INFORMATION Upe of Pit System: CLOSED Upe of Mud System: WATER Uportional System: Water Upo	lated by use of a to No Closed System Means S R BASED 5000 greater than 10ft below bar well? N	Surface (wo-stage cementing to Fresh Water Steel Pits	Casing: 0 tool from 1090 to r Supply Well Drilled: No Approved	Depth O 0 . Method for disposal of Drillin Commercial pit facility: Sec	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No ng Fluids:
Cement will be circul Under Federal Jurisdiction: IT 1 INFORMATION //pe of Pit System: CLOSED //pe of Mud System: WATER nlorides Max: 8000 Average: depth to top of ground water of ithin 1 mile of municipal water fellhead Protection Area? t is located in a Hydrol	lated by use of a to No Closed System Means S R BASED 5000 greater than 10ft below bar well? N	Surface (wo-stage cementing to Fresh Water Steel Pits	Casing: 0 tool from 1090 to r Supply Well Drilled: No Approved	Depth O 0 . Method for disposal of Drillin Commercial pit facility: Sec	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No ng Fluids: c. 19 Twn. 8N Rng. 5E Cnty. 125 Order No: 274874
nding CD Numbers: Total Depth: 4200 Cement will be circul Under Federal Jurisdiction: IT 1 INFORMATION ype of Pit System: CLOSED ype of Mud System: WATER hlorides Max: 8000 Average: depth to top of ground water of depth to top of ground water of fithin 1 mile of municipal water //ellhead Protection Area? it is located in a Hydrol ategory of Pit: C	lated by use of a to No Closed System Means S R BASED 5000 greater than 10ft below bar well? N N logically Sensitive Area.	Surface (wo-stage cementing to Fresh Water Steel Pits	Casing: 0 tool from 1090 to r Supply Well Drilled: No Approved	Depth O 0 . Method for disposal of Drillin Commercial pit facility: Sec	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No ng Fluids:
Cement will be circul Under Federal Jurisdiction: PIT 1 INFORMATION type of Pit System: CLOSED type of Mud System: WATER thlorides Max: 8000 Average: depth to top of ground water of dithin 1 mile of municipal water dellhead Protection Area?	lated by use of a to No Closed System Means Standard Report Standard Report Standard Report Standard Report Repor	Surface (wo-stage cementing to Fresh Water Steel Pits	Casing: 0 tool from 1090 to r Supply Well Drilled: No Approved	Depth O 0 . Method for disposal of Drillin Commercial pit facility: Sec	pecial Orders: to base of Treatable Water-Bearing FM: 990 Surface Water used to Drill: No ng Fluids:

Notes:

Category Description

ALTERNATE CASING

9/9/2013 - G71 - APPROVED WITH THE FOLLOWING CONDITIONS: (1) MUD UP PRIOR TO TD TO PROTECT SHALLOW SANDS, (2) 2-STAGE CEMENTING TOOL TO BE SET AT 100' BELOW BTW, & (3) COPY OF CBL NEEDS TO BE SUBMITTED TO THE TECHNICAL STAFF IMMEDIATELY. A COMPLETION ATTEMPT, IN CASES WHERE THE PROTECTION OF THE

TREATABLE WATER IS QUESTIONABLE, IS STRICTLY PROHIBITED. RULE 165: 10-3-4 (D)(4)(C)

SPACING 9/9/2013 - G30 - FORMATION UNSPACED, 40 ACRE LEASE (NW4 SE4)