# Oklahoma Corporation Commission Oil & Gas Conservation Division Post Office Box 52000 Oklahoma City, Oklahoma 73152-2000

Rule 165: 10-3-25

API No.: 35129238330001 **Completion Report** Spud Date: July 09, 2013

OTC Prod. Unit No.: 129-211254 Drilling Finished Date: August 06, 2013

1st Prod Date: November 05, 2013

Completion Date: November 05, 2013

Drill Type: **HORIZONTAL HOLE** 

Location:

Well Name: LEDDY 3-28H Purchaser/Measurer: ENABLE GATHERING &

PROCESSING LLC

Min Gas Allowable: Yes

First Sales Date: 11/05/2013

ROGER MILLS 28 16N 23W

SE SW SW SW 250 FSL 440 FWL of 1/4 SEC

Latitude: 35.82763 Longitude: -99.65714 Derrick Elevation: 0 Ground Elevation: 2100

APACHE CORPORATION 6778 Operator:

> 6120 S YALE AVE STE 1500 TULSA, OK 74136-4224

	Completion Type							
	X Single Zone							
	Multiple Zone							
Γ	Commingled							

Location Exception				
Order No				
611482				

Increased Density
Order No
614558

Casing and Cement									
Туре	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT		
SURFACE	9 5/8	40	J-55	691		493	SURFACE		
INTERMEDIATE	7	26	P 110	7850		527	1278		
PRODUCTION	4 1/2	11.6	P-110 HC	13046		414	6830		

Liner									
Туре	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth	
There are no Liner records to display.									

Total Depth: 13046

Packer					
Depth	Brand & Type				
There are no Packer records to display.					

Plug						
Depth	Plug Type					
There are no Plug records to display.						

December 12, 2013 1 of 2

	Initial Test Data									
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut- In Pressure	Choke Size	Flow Tubing Pressure
Nov 30, 2013	TONKAWA	98	41.7	46	469	249	GAS LIFT	1159	64/64	100

#### **Completion and Test Data by Producing Formation**

Formation Name: TONKAWA

Code: 406TNKW

Class: OIL

Spacing Orders						
Spacing Orders						
Order No Unit Size						
208270 640						

Perforated Intervals					
From	То				
8743	12870				

**Acid Volumes** 

There are no Acid Volume records to display.

Fracture	Treatments
----------	------------

10 STAGE FRAC; 704,500# TOTAL PROP; 15,864 BBL TLTR

Formation	Тор
DOUGLAS H TOP	7951
HASKELL	8329
TONKAWA FS	8385

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

### Other Remarks

OCC: FLE ORDER HAS NOT BEEN ISSUED. WE HAVE ACCEPTED OPERATORS DATA AS SUBMITTED. IRREGULAR SECTION.

### **Lateral Holes**

Sec: 28 TWP: 16N RGE: 23W County: ROGER MILLS

NE NW NW NW

200 FNL 600 FWL of 1/4 SEC

Depth of Deviation: 7883 Radius of Turn: 573 Direction: 5 Total Length: 4760

Measured Total Depth: 13046 True Vertical Depth: 8452 End Pt. Location From Release, Unit or Property Line: 200

## FOR COMMISSION USE ONLY

1121858

Status: Accepted

December 12, 2013 2 of 2