API NUMBER: 019 26030 A

OKLAHOMA CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION P.O. BOX 52000 OKLAHOMA CITY, OK 73152-2000 (Rule 165:10-3-1)

Approval Date:	01/08/2014
Expiration Date:	07/08/2014

Straight Hole Oil & Gas

Amend reason: OCC CORRECTION TO CHANGE ALTERNATE CASING REQUIREMENTS

## AMEND PERMIT TO DRILL

VELL LOCATION:	Sec:	09	Twp:	28	Rge:	2W	County	: CAR	TER		
SPOT LOCATION:	SE	SE	N'	W	NW		FEET FROM QUARTER:	FROM	NORTH	FROM	WEST
							SECTION LINES:		1215		1075

Lease Name: TATUMS DES MOINES Well No: 126 Well will be 415 feet from nearest unit or lease boundary.

Operator CITATION OIL & GAS CORPORATION Telephone: 2818911000 OTC/OCC Number: 14156 0

CITATION OIL & GAS CORPORATION

PO BOX 690688

HOUSTON, TX 77269-0688

CHARLES D MORRISON AND

P O BOX

BETH BLUBAUGH MORRISON

OKLAHOMA CITY OK 73113

Formation(s) (Permit Valid for Listed Formations Only):

	Name	Depth	Name	Depth
1	DES MOINES	1437	6	
2			7	
3			8	
4			9	
5			10	
Spacing Orders	: 59065	Location Exception Or	ders:	Increased Density Orders:

Pending CD Numbers: Special Orders:

Total Depth: 2200 Ground Elevation: 977 Surface Casing: 0 Depth to base of Treatable Water-Bearing FM: 940

## Cement will be circulated from Total Depth to the Ground Surface on the Production Casing String.

Under Federal Jurisdiction: No Fresh Water Supply Well Drilled: No Surface Water used to Drill: Yes

PIT 1 INFORMATION

Type of Pit System: ON SITE

Type of Mud System: WATER BASED

Chlorides Max: 5000 Average: 3000

Is depth to top of ground water greater than 10ft below base of pit? Y

Within 1 mile of municipal water well? N

Pit is located in a Hydrologically Sensitive Area.

Category of Pit: 2

Wellhead Protection Area?

Liner not required for Category: 2
Pit Location is BED AQUIFER
Pit Location Formation: WELLINGTON

D. One time land application -- (REQUIRES PERMIT) PERMIT NO: 14-26101

H. CBL REQUIRED

Approved Method for disposal of Drilling Fluids:

A. Evaporation/dewater and backfilling of reserve pit.

Notes:

Category Description

ALTERNATE CASING 1/15/2014 - G71 - APPROVED WITH THE FOLLOWING CONDITIONS: (1) MUD UP PRIOR TO TD

TO PROTECT SHALLOW SANDS, (2) 2-STAGE CEMENTING TOOL TO BE SET AT 100' BELOW BTW AND USED ONLY IF CEMENT IS NOT CIRCULATED TO SURFACE ON THE PRODUCTION CASING STRING, & (3) COPY OF CBL NEEDS TO BE SUBMITTED TO THE TECHNICAL STAFF IMMEDIATELY. A COMPLETION ATTEMPT, IN CASES WHERE THE PROTECTION OF THE TREATABLE WATER IS QUESTIONABLE, IS STRICTLY PROHIBITED. RULE 165: 10-3-4 (D)(4)(C)

FRAC FOCUS 1/8/2014 - G71 - THE REQUIREMENT FOR CHEMICAL DISCLOSURE OF HYDRAULIC

FRACTURING INGREDIENTS WILL BE EXTENDED TO INCLUDE ALL NON-HORIZONTAL WELLS FOR HYDRAULIC FRACTURING OPERATIONS BEGINNING JANUARY 1, 2014. REFER TO OCC RULE 165:10-3-10 FOR COMPLIANCE REQUIREMENTS. PLEASE REPORT DIRECTLY TO FRACFOCUS USING THE FOLLOWING LINK HTTP://FRACFOCUS.ORG/ OR FOR OCC

ASSISTANCE CONTACT DENNIS NISKERN AT 405-522-2977 OR D.NISKERN@OCCEMAIL.COM

SPACING - 59065 1/8/2014 - G30 - (UNIT) SE4 NW4 & NE4 SW4 NW4 & SE4 NW4 NW4 & W2 NE4 NW4 9-2S-2W

EST TATUMS DES MOINES UNIT FOR DSMN