API NUMBER: 019 26032 Α

## **OKLAHOMA CORPORATION COMMISSION OIL & GAS CONSERVATION DIVISION** P.O. BOX 52000 **OKLAHOMA CITY, OK 73152-2000** (Rule 165:10-3-1)

Approval Date: 01/08/2014 07/08/2014 Expiration Date:

406 feet from nearest unit or lease boundary.

14156 0

OTC/OCC Number:

Straight Hole Oil & Gas

PO BOX 690688

HOUSTON.

## DRILL

mend reason: OCC CORRECTION TO CHANGE ALTERNATE ASING REQUIREMENTS		AME	ND PERM	IT TO DRIL
WELL LOCATION: Sec: 09 Twp: 2S Rge: 2W  SPOT LOCATION: SE SW SE NW			OUTH FR	ом <b>EAST</b> 914
Lease Name: TATUMS DES MOINES	Well	l No: 1	23	
Operator CITATION OIL & GAS CORPORATION Name:	DN		Telephone	: 2818911000
CITATION OIL & GAS CORPORATION				

TX

77269-0688

JIMMIE L. GODWIN 1347 MOUNTAIN VIEW ROAD

Well will be

**SPRINGER** OK 73458

Formation(s) (Permit Valid for Listed Formations Only):

is located in a Hydrologically Sensitive Area.

	Name	Depth	Name	Depth
1	DES MOINES	1258	6	
2			7	
3			8	
4			9	
5			10	
Spacing Orders:	59065	Location Exception Orders:		Increased Density Orders:
Pendina CD Nun	nbers:			Special Orders:

Depth to base of Treatable Water-Bearing FM: 800 Total Depth: 2300 Ground Elevation: 970 Surface Casing: 0

## Cement will be circulated from Total Depth to the Ground Surface on the Production Casing String.

Under Federal Jurisdiction: No Fresh Water Supply Well Drilled: No Surface Water used to Drill: Yes Approved Method for disposal of Drilling Fluids: PIT 1 INFORMATION Type of Pit System: ON SITE A. Evaporation/dewater and backfilling of reserve pit. Type of Mud System: WATER BASED D. One time land application -- (REQUIRES PERMIT) PERMIT NO: 14-26098 Chlorides Max: 5000 Average: 3000 H. CBL REQUIRED Is depth to top of ground water greater than 10ft below base of pit? Y Within 1 mile of municipal water well? Wellhead Protection Area?

Notes:

Category of Pit: 2

Liner not required for Category: 2 Pit Location is BED AQUIFER Pit Location Formation: WELLINGTON Category Description

ALTERNATE CASING 1/15/2014 - G71 - APPROVED WITH THE FOLLOWING CONDITIONS: (1) MUD UP PRIOR TO TD

TO PROTECT SHALLOW SANDS, (2) 2-STAGE CEMENTING TOOL TO BE SET AT 100' BELOW BTW AND USED ONLY IF CEMENT IS NOT CIRCULATED TO SURFACE ON THE PRODUCTION CASING STRING, & (3) COPY OF CBL NEEDS TO BE SUBMITTED TO THE TECHNICAL STAFF IMMEDIATELY. A COMPLETION ATTEMPT, IN CASES WHERE THE PROTECTION OF THE TREATABLE WATER IS QUESTIONABLE, IS STRICTLY PROHIBITED. RULE 165: 10-3-4 (D)(4)(C)

FRAC FOCUS 1/8/2014 - G71 - THE REQUIREMENT FOR CHEMICAL DISCLOSURE OF HYDRAULIC

FRACTURING INGREDIENTS WILL BE EXTENDED TO INCLUDE ALL NON-HORIZONTAL WELLS FOR HYDRAULIC FRACTURING OPERATIONS BEGINNING JANUARY 1, 2014. REFER TO OCC RULE 165:10-3-10 FOR COMPLIANCE REQUIREMENTS. PLEASE REPORT DIRECTLY TO FRACFOCUS USING THE FOLLOWING LINK HTTP://FRACFOCUS.ORG/ OR FOR OCC

ASSISTANCE CONTACT DENNIS NISKERN AT 405-522-2977 OR D.NISKERN@OCCEMAIL.COM

SPACING - 59065 1/8/2014 - G30 - (UNIT) SE4 NW4 & NE4 SW4 9-2S-2W

EST TATUMS DES MOINES UNIT FOR DSMN

WATERSHED STRUCTURE 1/8/2014 - G71 - WELL WITHIN 1/2 MILE OF AN OKLAHOMA CONSERVATION COMMISSION

WATERSHED STRUCTURE. CONTACT THE LOCAL CONSERVATION DISTRICT OFFICE AT (580)

223-5865 PRIOR TO DRILLING