

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35073252360000

Completion Report

Spud Date: March 09, 2016

OTC Prod. Unit No.: 073-217550-0-0000

Drilling Finished Date: March 22, 2016

1st Prod Date: June 21, 2016

Completion Date: June 05, 2016

Drill Type: HORIZONTAL HOLE

Well Name: GILBERT 1706 6-21MH

Purchaser/Measurer:

Location: KINGFISHER 22 17N 6W
NW NW NW NW
233 FNL 195 FWL of 1/4 SEC
Latitude: 35.94095 Longitude: -97.83541
Derrick Elevation: 0 Ground Elevation: 1005

First Sales Date:

Operator: OKLAHOMA ENERGY ACQUISITIONS LP 23509

15021 KATY FWY STE 400
HOUSTON, TX 77094-1900

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception
Order No
649116

Increased Density
Order No
There are no Increased Density records to display.

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
CONDUCTOR	16		X42	125		27	SURFACE
SURFACE	9 5/8	36	J55	484		300	SURFACE
INTERMEDIATE	7	26	P110	7666		270	4822

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4 1/2	11.6	P110	4980	0	0	7525	

Total Depth: 12506

Packer	
Depth	Brand & Type
7496	ASIII

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Jul 20, 2016	MISS'AN (EX CHESTER)	554	39	1478	2668	1547	GAS LIFT		OPEN	229

Completion and Test Data by Producing Formation									
Formation Name: MISS'AN (EX CHESTER)				Code: 359MSNLC			Class: OIL		
Spacing Orders				Perforated Intervals					
Order No		Unit Size		From			To		
648651		640		There are no Perf. Intervals records to display.					
Acid Volumes				Fracture Treatments					
4741 BBLS HCL				268,913 BBLS SW; 3,541,000 LBS SAND					

Formation	Top
COTTAGE GROVE	5296
CHECKERBOARD	6053
CLEVELAND	6101
BIG LIME	6330
OSWEGO (4TH)	6468
PRUE	6543
VERDIGRIS	6578
SKINNER	6625
PINK LIME	6694
RED FORK	6739
INOLA	6775
CHESTER	6827
MERAMEC	6940
MLM	7280

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks
THIS WELL IS AN OPEN HOLE COMPLETION FROM THE BOTTOM OF THE 7" CASING AT 7666' TO TERMINUS AT 12,506'. THE 4 1/2" LINER IS NOT CEMENTED. IRREGULAR SECTION.

Lateral Holes
Sec: 21 TWP: 17N RGE: 6W County: KINGFISHER SW SW SE SE 202 FSL 1119 FEL of 1/4 SEC Depth of Deviation: 6996 Radius of Turn: 538 Direction: 182 Total Length: 4598 Measured Total Depth: 12506 True Vertical Depth: 7419 End Pt. Location From Release, Unit or Property Line: 202

FOR COMMISSION USE ONLY
Status: Accepted