

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35073253040000

Completion Report

Spud Date: July 04, 2016

OTC Prod. Unit No.: 073-217845-0-0000

Drilling Finished Date: July 22, 2016

1st Prod Date: September 16, 2016

Completion Date: August 13, 2016

Drill Type: HORIZONTAL HOLE

Well Name: BOECHER 1706 4-19MH

Purchaser/Measurer:

Location: KINGFISHER 19 17N 6W
SW NW NE NW
422 FNL 1388 FWL of 1/4 SEC
Latitude: 35.9408 Longitude: 97.88479
Derrick Elevation: 0 Ground Elevation: 1013

First Sales Date:

Operator: OKLAHOMA ENERGY ACQUISITIONS LP 23509

15021 KATY FWY STE 400
HOUSTON, TX 77094-1900

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception
Order No
657274

Increased Density
Order No
There are no Increased Density records to display.

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
CONDUCTOR	16		X42	125		27	SURFACE
SURFACE	9 5/8	36	J55	480		300	SURFACE
INTERMEDIATE	7	29	P110	7400		420	6400

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4 1/2	13.5	P110	5330	0	0	7284	12614

Total Depth: 12615

Packer	
Depth	Brand & Type
7244	ASIII

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Oct 15, 2016	MISS'AN (EX CHESTER)	494	39	572	1158	1243	GAS LIFT		OPEN	200

Completion and Test Data by Producing Formation										
Formation Name: MISS'AN (EX CHESTER)			Code: 359MSNLC			Class: OIL				
Spacing Orders				Perforated Intervals						
Order No		Unit Size		From			To			
653076		640		There are no Perf. Intervals records to display.						
Acid Volumes				Fracture Treatments						
5423 BBLS				282,323 BBLS SW; 4,844,984 LBS PROPPANT						

Formation	Top
COTTAGE GROVE	5736
HOGSHOOTER	6108
CHECKERBOARD	6191
CLEVELAND	6224
BIG LIME	6454
OSWEGO (4TH)	6599
PRUE	6677
VERDIGRIS	6714
SKINNER	6730
PINK LIME	6838
RED FORK	6882
INOLA	6928
BARTLESVILLE	6983
MANNING	7008
MERAMEC	7180
MLM	7476

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks
THIS WELL IS AN OPEN HOLE COMPLETION FROM THE BOTTOM OF THE SQUEEZED PERFS AT 7696' TO TERMINUS AT 12,615'. THE 4 1/2" LINER IS NOT CEMENTED. IRREGULAR SECTION. SQUEEZED PERFS FROM 7695' TO 7676' WITH 75 SACKS OF CEMENT.

Lateral Holes

Sec: 19 TWP: 17N RGE: 6W County: KINGFISHER

SW SW SW SE

205 FSL 11 FWL of 1/4 SEC

Depth of Deviation: 7147 Radius of Turn: 560 Direction: 179 Total Length: 4522

Measured Total Depth: 12615 True Vertical Depth: 7629 End Pt. Location From Release, Unit or Property Line: 205

FOR COMMISSION USE ONLY

1134689

Status: Accepted