

Oklahoma Corporation Commission  
Oil & Gas Conservation Division  
Post Office Box 52000  
Oklahoma City, Oklahoma 73152-2000  
Rule 165: 10-3-25

Form 1002A

API No.: 35151243660001

**Completion Report**

Spud Date: March 30, 2015

OTC Prod. Unit No.: 151-217989

Drilling Finished Date: April 08, 2015

1st Prod Date: October 20, 2016

**Amended**

Completion Date: October 12, 2016

Amend Reason: SHOW COMPLETION

**Drill Type: HORIZONTAL HOLE**

Min Gas Allowable: Yes

Well Name: HORSCH 5-28-16 2H

Purchaser/Measurer: CHESAPEAKE OPERATING LLC

Location: WOODS 5 28N 16W  
NW NE NW NW  
265 FNL 789 FWL of 1/4 SEC  
Derrick Elevation: 1830 Ground Elevation: 1808

First Sales Date: 10/20/2016

Operator: CHESAPEAKE OPERATING LLC 17441  
PO BOX 18496  
6100 N WESTERN AVE  
OKLAHOMA CITY, OK 73154-0496

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
636272	

Increased Density	
Order No	
636269	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13 3/8	48	H-40	498		381	SURFACE
INTERMEDIATE	9 5/8	36	J-55	1215		350	SURFACE
PRODUCTION	7	26	P-110EC	5762		211	4200

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4 1/2	11.6	P-110EC	4958	0	488	5557	10515

**Total Depth: 10515**

Packer	
Depth	Brand & Type
5490	AS-3

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Oct 25, 2016	MISSISSIPPI LIME	645		760	1178	1611	ARTIFICIA			220

Completion and Test Data by Producing Formation										
Formation Name: MISSISSIPPI LIME			Code: 351MSSLM			Class: OIL				
<b>Spacing Orders</b>				<b>Perforated Intervals</b>						
<b>Order No</b>	<b>Unit Size</b>			<b>From</b>			<b>To</b>			
545500	640			5752			10378			
<b>Acid Volumes</b>				<b>Fracture Treatments</b>						
8,000 GALLONS HCL ACID				38,263 BARRELS FRAC FLUID, 191,220 POUNDS PROPPANT						

Formation	Top
MISSISSIPPI LIME	5626

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks
OCC - THIS DOCUMENT IS ACCEPTED BASED ON THE DATA SUBMITTED THE FINAL LOCATION EXCEPTION HAS NOT BEEN SUBMITTED.

Lateral Holes
Sec: 5 TWP: 28N RGE: 16W County: WOODS
SW SW SW SE
195 FSL 2388 FEL of 1/4 SEC
Depth of Deviation: 5053 Radius of Turn: 433 Direction: 170 Total Length: 4889
Measured Total Depth: 10515 True Vertical Depth: 5486 End Pt. Location From Release, Unit or Property Line: 195

FOR COMMISSION USE ONLY
Status: Accepted
1134895