

Oklahoma Corporation Commission  
 Oil & Gas Conservation Division  
 Post Office Box 52000  
 Oklahoma City, Oklahoma 73152-2000  
 Rule 165: 10-3-25

Form 1002A

API No.: 35129240770001

**Completion Report**

Spud Date: August 18, 2016

OTC Prod. Unit No.: 12921786000000

Drilling Finished Date: September 05, 2016

1st Prod Date: September 29, 2016

Completion Date: September 29, 2016

**Drill Type: HORIZONTAL HOLE**

Well Name: TWO D RANCH 1H-36

Purchaser/Measurer: ENABLE GATHERING & PROCESSING

First Sales Date: 09/29/2016

Location: ROGER MILLS 36 17N 25W  
 NW NW NW NE  
 189 FNL 2330 FEL of 1/4 SEC  
 Latitude: 99.8160861 Longitude: 35.912186  
 Derrick Elevation: 0 Ground Elevation: 0

Operator: LE NORMAN OPERATING LLC 22738

4700 GAILLARDIA PKWY STE 200  
 OKLAHOMA CITY, OK 73142-1839

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception
Order No
652091

Increased Density
Order No
There are no Increased Density records to display.

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9 5/8	36#	J-55	1516		830	SURFACE
INTERMEDIATE	7"	26#	P-110	10055		575	1062

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4 1/2	15.1	P-110	4775	0	0	9543	14318

**Total Depth: 14318**

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Nov 09, 2016	CLEVELAND	126	45.8	554	4397	300	FLOWING		49/64	150

Completion and Test Data by Producing Formation										
Formation Name: CLEVELAND			Code: 405CLVD			Class: OIL				
<b>Spacing Orders</b>				<b>Perforated Intervals</b>						
<b>Order No</b>	<b>Unit Size</b>			<b>From</b>			<b>To</b>			
651614	640			10055			14318			
<b>Acid Volumes</b>				<b>Fracture Treatments</b>						
47 BBLs 15% HCL ACID				3,345,130 #S 40/70 OTTAWA SAND 75,680 BBLs SLICK WATER						

Formation	Top
HOGSHOOTER	8952
CHECKERBOARD	8994
CLEVELAND	9351

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks
OCC: FLE ORDER HAS NOT BEEN ISSUED. WE HAVE ACCEPTED OPERATORS DATA AS SUBMITTED. IRREGULAR SECTION. OPEN HOLE FROM 10055' TO TOTAL DEPTH OF 14318'. IRREGULAR SECTION.

Lateral Holes
Sec: 36 TWP: 17N RGE: 25W County: ROGER MILLS
SW SW SW SE
165 FSL 2500 FEL of 1/4 SEC
Depth of Deviation: 9070 Radius of Turn: 580 Direction: 180 Total Length: 4936
Measured Total Depth: 14318 True Vertical Depth: 9793 End Pt. Location From Release, Unit or Property Line: 165

FOR COMMISSION USE ONLY
Status: Accepted
1134887