

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35081242740000

Completion Report

Spud Date: September 20, 2016

OTC Prod. Unit No.: 081-217955-0-0000

Drilling Finished Date: September 29, 2016

1st Prod Date: November 14, 2016

Completion Date: November 11, 2016

Drill Type: HORIZONTAL HOLE

Well Name: SLOAN 24-16N-03E 1MH

Purchaser/Measurer:

Location: LINCOLN 13 16N 3E
NE SE SW SW
466 FSL 1270 FWL of 1/4 SEC
Derrick Elevation: 1005 Ground Elevation: 982

First Sales Date:

Operator: WHITE STAR PETROLEUM LLC 23358
PO BOX 13360
301 NW 63RD ST STE 600
OKLAHOMA CITY, OK 73113-1360

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
654936	

Increased Density	
Order No	
654972	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9-5/8"	36#	J-55	625		255	SURFACE
PRODUCTION	5-1/2"	17#	HCP-110	9708		915	3550

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 9708

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
9597	FRAC PLUG

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Nov 22, 2016	MISSISSIPPIAN	78		326	4179	846	PUMPING			

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPIAN

Code: 359MSSP

Class: OIL

Spacing Orders

Order No	Unit Size
653521	640

Perforated Intervals

From	To
4982	9577

Acid Volumes

1450 BLS ACID

Fracture Treatments

91,783 BLS WATER
3,620,356 LBS SAND

Formation	Top
MISSISSIPPIAN	4454

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OCC: FLE ORDER HAS NOT BEEN ISSUED. WE HAVE ACCEPTED OPERATORS DATA AS SUBMITTED. IRREGULAR SECTION.

Lateral Holes

Sec: 24 TWP: 16N RGE: 3E County: LINCOLN

SE SW SW SW

168 FSL 546 FWL of 1/4 SEC

Depth of Deviation: 3774 Radius of Turn: 1267 Direction: 181 Total Length: 4667

Measured Total Depth: 9708 True Vertical Depth: 4532 End Pt. Location From Release, Unit or Property Line: 168

FOR COMMISSION USE ONLY

1135216

Status: Accepted