

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35081242710000

Completion Report

Spud Date: August 30, 2016

OTC Prod. Unit No.: 081-217938-0-0000

Drilling Finished Date: September 10, 2016

1st Prod Date: November 20, 2016

Completion Date: November 19, 2016

Drill Type: HORIZONTAL HOLE

Well Name: THOMAS 24-16N-3E 1MH

Purchaser/Measurer:

Location: LINCOLN 24 16N 3E
NW NE NW NE
231 FNL 1802 FEL of 1/4 SEC
Derrick Elevation: 1002 Ground Elevation: 979

First Sales Date:

Operator: WHITE STAR PETROLEUM LLC 23358
PO BOX 13360
301 NW 63RD ST STE 600
OKLAHOMA CITY, OK 73113-1360

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
654032	

Increased Density	
Order No	
There are no Increased Density records to display.	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	9-5/8"	36#	J-55	635		255	SURFACE
PRODUCTION	5-1/2"	17#	HCP-110	9021		830	3800

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

Total Depth: 9021

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
8908	FRAC PLUG

Initial Test Data										
Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Dec 04, 2016	MISSISSIPPIAN	39		148	3795	568	PUMPING			

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPIAN

Code: 359MSSP

Class: OIL

Spacing Orders

Order No	Unit Size
653521	640

Perforated Intervals

From	To
4932	8890

Acid Volumes

1446 BLS ACID

Fracture Treatments

94,122 BLS WATER
3,606,250 LBS SAND

Formation	Top
MISSISSIPPIAN	4418

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

OCC: FLE ORDER HAS NOT BEEN ISSUED. WE HAVE ACCEPTED OPERATORS DATA AS SUBMITTED. IRREGULAR SECTION.

Lateral Holes

Sec: 24 TWP: 16N RGE: 3E County: LINCOLN

SW SE SW SE

166 FSL 1944 FEL of 1/4 SEC

Depth of Deviation: 3710 Radius of Turn: 1280 Direction: 177 Total Length: 4031

Measured Total Depth: 9021 True Vertical Depth: 4523 End Pt. Location From Release, Unit or Property Line: 166

FOR COMMISSION USE ONLY

1135315

Status: Accepted