

Oklahoma Corporation Commission
Oil & Gas Conservation Division
Post Office Box 52000
Oklahoma City, Oklahoma 73152-2000
Rule 165: 10-3-25

Form 1002A

API No.: 35073253070000

Completion Report

Spud Date: September 05, 2016

OTC Prod. Unit No.: 073-218090-0-0000

Drilling Finished Date: September 19, 2016

1st Prod Date: November 21, 2016

Completion Date: October 31, 2016

Drill Type: HORIZONTAL HOLE

Well Name: MITCHELL 1806 2B-27MH

Purchaser/Measurer:

Location: KINGFISHER 22 18N 6W
SW SW SE SW
255 FSL 1527 FWL of 1/4 SEC
Latitude: 36.0155 Longitude: 97.83072
Derrick Elevation: 0 Ground Elevation: 1170

First Sales Date:

Operator: OKLAHOMA ENERGY ACQUISITIONS LP 23509

15021 KATY FWY STE 400
HOUSTON, TX 77094-1900

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
652957	

Increased Density	
Order No	
There are no Increased Density records to display.	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
CONDUCTOR	16		X42	123		27	SURFACE
SURFACE	9 5/8	36	J55	473		300	SURFACE
INTERMEDIATE	7	29	P110	7608		285	4800

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4 1/2	13.5	P110	5037	0	0	7421	12458

Total Depth: 12460

Packer	
Depth	Brand & Type
7395	ASIII

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Dec 25, 2016	MISS'AN (EX CHESTER)	259	39	231	892	1080	GAS LIFT		OPEN	96

Completion and Test Data by Producing Formation

Formation Name: MISS'AN (EX CHESTER)

Code: 359MSNLC

Class: OIL

Spacing Orders

Order No	Unit Size
651894	640

Perforated Intervals

From	To
There are no Perf. Intervals records to display.	

Acid Volumes

7459 BBLS HCL

Fracture Treatments

241,362 BBLS SW; 6,019,200 LBS SAND

Formation	Top
COTTAGE GROVE	5716
HOGSHOOTER	6058
CHECKERBOARD	6111
CLEVELAND	6131
BIG LIME	6323
OSWEGO (4TH)	6445
PRUE	6525
VERDIGRIS	6561
SKINNER	6573
PINK LIME	6668
RED FORK	6709
INOLA	6756
MANNING	6800
MRMC	6965
MLM	7221

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

THIS WELL IS AN OPEN HOLE COMPLETION FROM THE BOTTOM OF THE 7" CASING AT 7608' TO TERMINUS AT 12,460'. THE 4 1/2" LINER IS NOT CEMENTED.
OCC: FLE ORDER HAS NOT BEEN ISSUED. WE HAVE ACCEPTED OPERATORS DATA AS SUBMITTED.
IRREGULAR SECTION.

Lateral Holes

Sec: 27 TWP: 18N RGE: 6W County: KINGFISHER

SW SW SE SW

206 FSL 1362 FWL of 1/4 SEC

Depth of Deviation: 6950 Radius of Turn: 438 Direction: 176 Total Length: 4740

Measured Total Depth: 12460 True Vertical Depth: 7464 End Pt. Location From Release, Unit or Property Line: 206

FOR COMMISSION USE ONLY

1135382

Status: Accepted