

Oklahoma Corporation Commission  
Oil & Gas Conservation Division  
Post Office Box 52000  
Oklahoma City, Oklahoma 73152-2000  
Rule 165: 10-3-25

Form 1002A

API No.: 35043235680000

**Completion Report**

Spud Date: November 15, 2017

OTC Prod. Unit No.: 043-222894

Drilling Finished Date: January 03, 2018

1st Prod Date: January 31, 2018

Completion Date: January 23, 2018

**Drill Type: HORIZONTAL HOLE**

Min Gas Allowable: Yes

Well Name: BIVENS 7-19-17 1H

Purchaser/Measurer: ENABLE

Location: DEWEY 18 19N 17W  
NW NW NW NE  
240 FNL 2495 FEL of 1/4 SEC  
Latitude: 36.12917408 Longitude: -99.0523201  
Derrick Elevation: 1938 Ground Elevation: 1908

First Sales Date: 01/31/2018

Operator: TAPSTONE ENERGY LLC 23467

100 E MAIN ST  
OKLAHOMA CITY, OK 73104-2509

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
677719	

Increased Density	
Order No	
670790	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
SURFACE	13 3/8	54.5	J-55	1515	900	1040	SURFACE
INTERMEDIATE	9 5/8	40	P-110	10903	1950	2075	SURFACE
PRODUCTION	5 1/2	20	P-110	16748	9000	880	11052

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
There are no Liner records to display.								

**Total Depth: 16748**

Packer	
Depth	Brand & Type
11532	AS1-X

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Feb 26, 2018	MISSISSIPPIAN	620	50	4752	7665	1588	FLOWING		48	997

**Completion and Test Data by Producing Formation**

Formation Name: MISSISSIPPIAN

Code: 359MSSP

Class: OIL

**Spacing Orders**

Order No	Unit Size
657193	640

**Perforated Intervals**

From	To
11861	16748

**Acid Volumes**

948 BARRELS 15% HCL

**Fracture Treatments**

147,580 BARRELS, 3,981,757 POUNDS PROPPANT

Formation	Top
BASE HEEBNER SHALE	6574
BASE DOUGLAS SANDS	6936
TONKAWA SAND	7019
TOP COTTAGE GROVE SAND	7479
HOGSHOOTER	7799
OSWEGO LIME	8159
ATOKA	8799
MISSISSIPPIAN / CHESTER LIME	9367

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

**Other Remarks**

There are no Other Remarks.

**Lateral Holes**

Sec: 7 TWP: 19N RGE: 17W County: DEWEY

NW NW NW NE

196 FNL 2174 FEL of 1/4 SEC

Depth of Deviation: 11127 Radius of Turn: 851 Direction: 6 Total Length: 5621

Measured Total Depth: 16748 True Vertical Depth: 11447 End Pt. Location From Release, Unit or Property Line: 196

**FOR COMMISSION USE ONLY**

1139606

Status: Accepted