

Oklahoma Corporation Commission
 Oil & Gas Conservation Division
 Post Office Box 52000
 Oklahoma City, Oklahoma 73152-2000
 Rule 165: 10-3-25

Form 1002A

API No.: 35017255180000

Completion Report

Spud Date: November 19, 2019

OTC Prod. Unit No.: 017-226713-0-0000

Drilling Finished Date: January 02, 2020

1st Prod Date: March 27, 2020

Completion Date: March 19, 2020

Drill Type: HORIZONTAL HOLE

Well Name: PAMUNKEY 14-12N-7W 7MH

Purchaser/Measurer: ANCOVA

Location: CANADIAN 11 12N 7W
 NW SW SE SW
 605 FSL 1545 FWL of 1/4 SEC
 Latitude: 35.524089206 Longitude: -97.913837052
 Derrick Elevation: 1344 Ground Elevation: 1324

First Sales Date: 3/27/2020

Operator: PALOMA OPERATING CO INC 23932

1100 LOUISIANA ST STE 5100
 HOUSTON, TX 77002-5220

Completion Type	
X	Single Zone
	Multiple Zone
	Commingled

Location Exception	
Order No	
713152	

Increased Density	
Order No	
701139	

Casing and Cement							
Type	Size	Weight	Grade	Feet	PSI	SAX	Top of CMT
CONDUCTOR	20	52.78	X42	107			SURFACE
SURFACE	9.625	36	J-55	1464		435	SURFACE
PRODUCTION	7	29	P-110	9338		335	4469

Liner								
Type	Size	Weight	Grade	Length	PSI	SAX	Top Depth	Bottom Depth
LINER	4.5	13.5	P-110	5684	0	350	9124	14808

Total Depth: 14850

Packer	
Depth	Brand & Type
There are no Packer records to display.	

Plug	
Depth	Plug Type
There are no Plug records to display.	

Initial Test Data

Test Date	Formation	Oil BBL/Day	Oil-Gravity (API)	Gas MCF/Day	Gas-Oil Ratio Cu FT/BBL	Water BBL/Day	Pumpin or Flowing	Initial Shut-In Pressure	Choke Size	Flow Tubing Pressure
Mar 28, 2020	MISSISSIPPIAN	944	45.59	2291	2427	1538	FLOWING	10	32/64	859

Completion and Test Data by Producing Formation

Formation Name: MISSISSIPPIAN

Code: 359MSSP

Class: OIL

Spacing Orders

Order No	Unit Size
141057	640

Perforated Intervals

From	To
9816	14660

Acid Volumes

NONE

Fracture Treatments

155,552 BBLs FLUID 11,236,853 LBS PROPPANT

Formation	Top
MERAMEC	9342

Were open hole logs run? No

Date last log run:

Were unusual drilling circumstances encountered? No

Explanation:

Other Remarks

There are no Other Remarks.

Lateral Holes

Sec: 14 TWP: 12N RGE: 7W County: CANADIAN

SE SW SW SW

66 FSL 563 FWL of 1/4 SEC

Depth of Deviation: 8868 Radius of Turn: 724 Direction: 183 Total Length: 4844

Measured Total Depth: 14850 True Vertical Depth: 9213 End Pt. Location From Release, Unit or Property Line: 66

FOR COMMISSION USE ONLY

Status: Accepted

1144846